Weld Compact-

Maybe up to 111" for FWD cars, 107” for RWD cars. 6 cylinder and less only. Leave VIN tag intact, to verify wheelbase.

1. ALL GENERAL RULES APPLY, WITH THESE EXCEPTIONS.

2. All parts must be of compact origin, except bumpers and rims.

3. Full-size bumpers allowed, may be seam welded and stuffed. Must be trimmed to width of car.

4. If you don’t use or have the factory bumper shock, you may use a 2”x 2”x8” maximum square or round pipe. Call with questions.

5. You may wire windows in 1 place per window opening. Must remain within that window. Wire may go from a window to the frame in no more than 4 places. Washers may be welded in place to support the wire, 2" max. Welded to sheet metal only, not to the frame.

6. Maximum of 5 leafs per side. Must be factory thickness and have factory step-down. No leaf conversions.

7. Compact differentials only.

8. Aftermarket engine cradles allowed no “extreme” setups. Call with questions.

9. Distributor protectors, carb protectors, trans brace, valve cover protectors, fuel pump protectors, etc. are allowed, but cannot strengthen car or come into contact with any cage component at any time before/during/after the event. Call with questions.

10. Tie rod ends may be reinforced, but must start with originals (not home-made). A-arms may be bolted or welded with two 2” straps. Do not weld struts to the frame in any way.

11. Only seam welding allowed is top uni-bodyseam center of the A-arm forward. No interior seem welding.

12. K-frames may be welded to uni-body no added material. Do not seem weld the K frame!

13. Door and trunk seams may be chained, wired, or welded shut, 5" maximum weld, 5" min. gaps. 5-3/8” bolts are allowed in the drip rail.

14. Hood may be chained, wired, or bolted shut (pick only one). Max of six 1” hood pins with 6" maximum washers. Only two may go to frame. They may be welded in place.

15. Trunk may use up to four 3/4" ready rod with 4" max washers that may go to frame. They may be welded in place. May also be welded shut also, 5" on, 5" off.

16. Back window bar is allowed 2”X2” max. 6”X6” attachment plates may be bolted or welded to roof (flush with window opening) and centered on trunk/speaker deck seam. Call with questions